



Stufe 1 Luftreinigung

In der ersten Stufe wird die Luft durch einen Grob- und Feinstaubfilter gesogen. Dieser entfernt Schmutz und Schwebepartikel sowie Pollen und Rauchpartikel.

Stufe 2 Geruchseliminierung

In der zweiten Stufe werden Tabak/Rauch-, Schweiß-, Sanitär-, Küchengerüche etc. mit airomex® konsequent und endgültig aus der Luft entfernt.

Der Luft wird airomex® beigefügt, ein Geruchsneutralisator, der geruchsneutral und natürlich (Glycinbetain) ist. Dieser dockt sich an das negative Geruchsmolekül und wandelt es sofort in ein Neutralsalz um.

Stufe 3 Botenstoffe

In der dritten Stufe wird die Luft mit natürlichen Botenstoffen (ätherischen Ölen) angereichert. In der Regel unter der Wahrnehmungsgrenze.

Stage 1 Air Cleansing

In the first stage the air is sucked through coarse and fine dust filters. These remove all dust and suspended particles, as well as pollen and smoke particles.

Stage 2 Smell Elimination

In the second stage, with the aid of airomex®, tobacco/smoke, perspiration, sanitary, kitchen and other smells are consistently and permanently removed from the air.

This odourless and natural glycine smell neutraliser attaches itself to the negative smell molecules and neutralises them.

Stage 3 Messenger Substances

During the third stage, the air is enriched with natural messenger substances (essential oils etc.). Generally speaking, these are usually beyond our perceptive levels.



Weiss
White



Schwarz
Black

Air Creative Premium Typ3300

Technische Daten

Gerätetyp	Premium 3300
Besonderheiten	Wandeinbaugerät
Beduftungskapazität	max. 800 m ³
Höhe	275 mm
Breite x Tiefe oder Durchmesser	600 x 140 mm
Gewicht	6,6 kg
Lautstärke bei 4.5 V (1 Meter)	35 dB
Lautstärke bei 12 V (1 Meter)	48 dB
Elektroanschluss	240 V / 40 VA
Max. Leistung	10.1 W
Artikelnummer	110160
Neutralisation	2
Botenstoffe	2
airomex®-Botenstoffmischung	–
airomex® Fertigmischung	–

Technical description

Appliance type	Premium 3300
Special features	wall installed appliance
Scenting capacity	max. 800 m ³
Height	275 mm
Width x depth or diameter	600 x 140 mm
Weight	6,6 kg
Volume at 4.5 V (1 metre)	35 dB
Volume at 12 V (1 metre)	48 dB
Electrical connection	240 V / 40 VA
Maximum power	10.1 W
Artide number	110160
Neutralisation	2
Messenger substances	2
airomex® messenger substance mixture	–
airomex® ready-to-use mixture	–